



Network Video Recorder

Model :FLNVRPRO8032

Input : 32 Channel @ 8MP
Bandwidth : 160 Mbps
HDD : 2no. HDD Support
HDMI Output : 4K

SPECIFICATIONS

Input:	32 channel 1080p channels @ 25fps.
Human/Vehicle Analysis:	16-ch
IP Video Input:	32-ch
Incoming Bandwidth:	160 Mbps
Outgoing Bandwidth:	160 Mbps
HDMI Output:	1-ch, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA Output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz
Video Output Mode:	HDMI/VGA independent output
Audio Output:	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)
Two-Way Audio	1-ch, RCA / 3.5mm Jack (Linear, 1 KΩ)
Decoding Format	H.265/H.264
Recording Resolution :	8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/Q CIF
Synchronous playback:	16-ch
Decoding Capability:	AI on 2-ch@8MP (30 fps)/4- ch@4 MP (30 fps)/8-ch@1080p (30 fps)AI off: 2-ch@12MP (30 fps)/3-ch@8 MP (30 fps)/6- ch@4 MP (30 fps)/12-ch@1080p (30 fps)
Stream Type:	Video, Video& Audio
Audio Compression :	G.711ulaw/G.711alaw/G.722/G.726/AAC
Remote Connection :	128
Network Protocol:	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP,SADP, SMTP, SNMP, NFS, iSCSI, SISTP,UPnP, HTTP, HTTPS
Network	Interface 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each HDD
USB Front panel:	1 × USB 2.0; Rear panel: 1 × USB2.0
Power Supply	12 VDC, 3.3 A
Consumption	≤ 15 W (withoutHDD)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%